



### SECURE STACK CIX/CAX



### SECURE STACK PRO



### GREASE DUCT



### SECURE SEAL

- The CIX, with its 2" densely packed insulation, and CAX, with 2" of air, ensure low heat loss and maximum possible draft.

- CIX: certified at 1" clearance to combustibles and 2" for grease ducting applications; CAX: certified at 4" clearance to combustibles.

- Thick-gauge 304 or 316 stainless steel inner liner provides a strong and more rigid assembly.

- Patented self-centering assembly system combined with low weight simplifies and accelerates installation.

- Coupling configuration requires only one locking band on outside of pipe and the use of a regular, less-expensive high-temperature silicone sealant.

- Outside casing available in 304 or 316 stainless steel as well as Galvalume® (Aluminum-zinc coated) material for a lower-cost option.

- Available in sizes from 5" to 36" diameters.

- Tested and listed to:  
UL-103  
ULC-ORD959  
ULC-S604  
UL-1978

- 1-year and 15-year limited warranty options available.

- Thick-gauge 304 or 316 stainless steel inner liner that provides a strong and more rigid assembly.

- Outer casing available in 304 or galvalume. Centering flue extension that simplify installation in any direction.

- Modular design assembles quickly with common tools.

- Available in sizes from 5" to 36" diameters.

- Tested and listed to:  
UL 103  
UL 103HT  
ULC S604  
ULC C959  
UL 1978  
UL 2221 - CIX3Z only  
CAN/ULC S662  
UL 2561 - except CIX3Z  
UL 1777 - SCL only  
CAN/ULC S635

- 1-year and 15-year limited warranty options available.

- Stainless steel construction is highly corrosion resistant and extremely durable.

- Round tubular design maintains structural integrity significantly longer than a rectangular welded steel product.

- 0" Clearance grease duct (3" insulation & 2 hours fire rating eliminates the need for a separate fire-rated enclosure around the duct.

- Inner casing available in 304 or 316 stainless steel.

- Outer casing available in 304 or galvalume.

- Superior flow rate is achieved with round tube construction.

- Modular design assembles quickly with common tools.

- Contaminants of combustion are not trapped within the flue like it is commonly found in the corners of a rectangular design, thus making it much easier to clean and reduce the chance of fire from accumulated grease.

- No safety concerns with having welding on site that could cause a fire.

- Available in sizes from 5" to 36" diameters.

- Tested and listed to:  
UL 1978  
UL 2221

- Backed by a comprehensive Limited Lifetime Warranty.

- Single and double wall for use with Categories I, II, III and IV gas-fired appliances, high-efficiency gas boilers, furnaces, booster heaters, pool heaters, water heaters, unit heaters or tankless water heaters.

- Listed as Type BH gas vent systems for appliances having a rated operating flue temperature of 480°F.

- Type L-Vent (SSD only) for venting listed SAS or oil fired appliances certified with Type L low temperature venting system.

- Flex features a smooth inner wall that provides for no output reduction, while supporting system's overall strength. Built-in draw latches provide quick and easy tool-free assembly and disassembly, requiring less time on the job site.

- Viton-seals more resistant than silicone against chemicals such as sulfuric acid often found in condensate

- AL29-4C® stainless steel resists the extreme corrosive environments found in condensing boilers, assuring trouble-free operation and longer product life.

- Available in sizes from 3" to 24" diameters for SS, SSD, SSID, and FLEX. 26" to 36" diameters for LDCC/LDCD.

- Tested and listed to:  
UL-1738  
ULC-S636

- 15-year warranty.